

AMENDMENTS TO SPECIFICATION:

Page 1, change the Title to read:

TRANSFER GRIPPER FOR A GRIPPER RAPIER WEAVING LOOM

Page 1, before the first paragraph, the following headings are inserted:

A. BACKGROUND OF THE INVENTION

1. Field

Page 1, before the second paragraph, the following heading is inserted:

2. Related Art

Page 1, the second paragraph is amended to read:

In modern rapier weaving looms, the transfer grippers, located on a rapier band or rapier rod, are moved at very high speeds. They must be braked down from this high speed when they reach the transfer point where a receiving gripper takes over the weft yarn. Because of its inertia, it can happen that the weft yarn moves onward, so that the piece of yarn to be taken over by the receiving gripper moves away from its specified position. It can then happen that the receiving gripper will not grasp the weft yarn, causing a weft ~~flaw~~ fault. The risk that the piece of yarn to be taken over will come loose can also occur, especially with heavy weft yarns, even if a properly functioning yarn brake is provided on the insertion side, since the forces of inertia stretch the weft yarn elastically downstream of the yarn brake.

Page 1, the third paragraph is amended to read:

A piece of yarn to be taken over by a receiving gripper is prevented from coming loose if this piece is held between two yarn clamps (British patent specification GB 14 87 897 ~~disclosure 1487897~~). In this kind of construction, two identical yarn clamps are provided, which are loaded by the same spring element. The piece of yarn located between the two yarn clamps and meant to be taken over by the receiving gripper will not move out of range of the specified position even

upon braking down from high speeds. The receiving gripper has a hooklike head with which it must reach behind the piece of yarn that is held between the two yarn clamps. In the process, the hooklike head deflects the piece of yarn, which then moves backward behind the hook when the hooklike head is moved past that piece of yarn. This deflection, if the weft yarns are not very elastic and/or have only relatively low strength, can cause the piece of yarn to become damaged or destroyed, so that the piece cannot be grasped then, and a weft fault occurs.

Page 2, before the first paragraph, the following heading is inserted:

B. BRIEF SUMMARY OF THE INVENTION

Page 2, the first paragraph is amended to read:

The object of the invention is to ~~embody~~ provide a transfer gripper of the type described above ~~defined at the outset~~ in such a way that deflection of the piece of yarn between the two yarn clamps will not cause any damage and/or destruction of that piece.

Page 2, the second paragraph is amended to read:

This object is attained in that a clamp element that is ~~resilient~~ resiliently yieldable in response to tensile force occurring in the length of yarn and to permit deflection of the length of yarn is provided.

Page 2, the third paragraph is amended to read:

The yarn clamps securely hold the weft yarn that they clamp in extended and tensioned condition, even at high forces of deceleration, so that the piece of yarn does not move away from its specified position. The deflection of the piece of yarn caused by the hooklike element of the receiving gripper generates additional tensile forces in that piece; because of these forces, the ~~resilient~~ resiliently yieldable element yields in such a way that excessive stress on the piece of yarn is avoided. Once the receiving gripper has entered far enough into the receiving gripper that the hooklike element engages the piece of yarn from behind, the deflection of the piece

of yarn is reversed as the ~~resilient~~ resiliently yieldable element moves back into its basic position. In the process the piece of yarn is tensioned again, so that it securely moves behind the hooklike element and is grasped.

Page 2, before the fourth paragraph, the following heading is inserted:

C. DESCRIPTION OF THE DRAWINGS

Page 3, before the fourth paragraph, the following heading is inserted:

D. DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS OF THE INVENTION

Page 3, the fourth paragraph is amended to read:

The transfer gripper 1 shown in the drawings as an exemplary embodiment corresponds in its basic construction to the transfer gripper described in U.S. Patent No. 6,227,259, the ~~International Patent Disclosure WO 99/18274~~. ~~The description of which in WO 99/18274~~ is hereby incorporated by reference. In the present application, the same reference numerals are used. In addition, the transfer gripper 1 of the invention is equipped with a second, uncontrolled yarn clamp 50, whose function will be explained hereinafter. This additional yarn clamp is formed by a clamp element 51, embodied as a leaf spring, and the inner face of the portion 6 of the transfer gripper 1 that forms the top side of the base body. The spring-elastic clamp element 51 is fastened to the portion 4 that forms the bottom of the base body. In the exemplary embodiment, this fastening is done by means of two screws 45, with which the base body of the transfer gripper 1 is mounted on a rapier band 2. The clamp element 51 designed as a leaf spring extends outwardly and forwardly ~~is lengthened outward~~, past the clamping location of the yarn clamp 50, and includes ~~with~~ a guide element 52 that extends forward toward the front end of the transfer gripper 1 along its direction of motion and is bent away to the side and downward. This guide element 52 serves to assure that a weft yarn 25 will securely reach the region of the clamping location 53 of the yarn clamp 50.

Page 3, the fifth paragraph is amended to read:

When the transfer gripper 1 approaches the place where the weft yarn 25 is taken over by a receiving gripper, a very sharp deceleration from high speed takes place down to a standstill. There is then the risk that the weft yarn, because of its inertia, will move away from the region of the stop 23 and move forward in the direction of the front end of the receiving gripper 1, as is shown in Fig. 2. The weft yarn 25 then leaves its predetermined position, so that there is the risk that it will not be grasped by a receiving gripper. This risk is minimized ~~encountered~~ by the yarn clamp 50, which holds the weft yarn 25 in the region of the stop 23 of the guide 22. The clamping force with which the yarn clamp 50 holds the weft yarn 25 is relatively slight, since it needs to prevent ~~present~~ only a motion of the weft yarn 25 counter to the forces of inertia that occur upon deceleration. It is also therefore designed to have a low value, since it must be readily possible for the receiving gripper to pull the weft yarn that it grasps out of the yarn clamp 50. For this yarn clamp 50, there is accordingly no need to provide an opening device. The clamping location 53 of the yarn clamp 50 is located somewhat ahead of the stop 23 of the guide 22 in terms of the direction of advancing motion of the transfer gripper. It is thus attained above all that only little dust development is to be expected. Any dust that occurs cannot settle, because of the open structure of the yarn clamp 50.

Page 4, the second full paragraph is amended to read:

To permit the deflection of the piece of the weft yarn 25 and also its return motion into the taut position without there being the risk of damage to the weft yarn 25, the yarn clamp 50 is embodied such that a ~~the~~ resiliently yielding clamp element 51 of the clamp 50 yields in the opening direction when an additional tensile force is introduced in the piece of yarn located between the two yarn clamps 15, 16 and 50. This yielding is represented by dashed lines in Fig. 5. Since the additional tensile force disappears again once the hooklike attachment 56 has moved past the piece of the weft yarn 25, the resiliently yielding clamp element 51 moves back into the closing position, so that the piece of yarn is tensioned again and securely comes to be located behind the hooklike protrusion 56. In the embodiment of Fig. 5, the

opening of the yarn clamp 50 is effected only very briefly, so that the weft yarn 25 does not have the opportunity during this period of time to move out of the yarn clamp 50.

Page 5, the first full paragraph is amended to read:

For the yarn clamp 50, many different designs are possible. Care must merely be taken to assure that the elements of this yarn clamp 50 do not hinder the penetration of the head 55 of a receiving gripper. In a modified embodiment, the stationary clamping face is a separate component, which is fastened to the base body of the transfer gripper 1. In a further-modified embodiment, ~~it is provided that~~ the yarn clamp 50 is designed such that it makes the travel distance[[,]] required to compensate for the deflection of the piece of the weft yarn 25[[,]] available without the yarn clamp 50 opening completely. A yarn clamp 50 with this function is shown in Fig. 6. The spring-elastic clamp element 51' has a clamping face that is relatively wide in the direction of motion of the transfer gripper 1, and it is moreover designed such that it can deform elastically, in the form of torsion, about a longitudinal axis extending along the traveling direction of the transfer gripper. As shown in Fig. 6, to compensate for the deflection by the head 55 of the receiving gripper, this clamping face is only tilted, so that the clamping action is not undone entirely.

Page 5, the second full paragraph is amended to read:

In the embodiment of Fig. 7, ~~it is provided that~~ the yarn clamp 50 has two movable clamp elements 53, 54, which are located side by side. The inner clamp element 54, that is, the clamp element oriented toward the yarn clamp 15, 16 that holds the end of the weft yarn 25, is designed such that when tensile forces occur in the piece of yarn, it yields elastically to the position shown in dashed lines. Conversely, the clamp element 53 is stiffer, so that the part of the yarn clamp 50 formed by this clamp element is not opened. To achieve these different spring stiffnesses, two clamp elements 53, 54, designed and fastened independently of one another, may be provided instead of the one-part element. Also in this embodiment, it may be provided that the clamp elements 53, 54 act not directly on

U.S. Patent Application No. 10/528,409
Attorney Docket: VERC3005/JEK

the base body 6 but rather on a clamping piece mounted on the base body 6. In a modified embodiment, it is provided that the elastic element that yields upon tensile forces in the piece of yarn, for instance the element 54, does not clamp the weft yarn 25, but only deflects it. This kind of elastic element is then, in a modified embodiment, located in the vicinity of the yarn clamp 15, 16 or of the deflector 13.